Appln. No. 10/685,687 Amdt. dated August 2, 2006 Reply to Office Action of April 4, 2006

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings of claims in the application:

Listing of Claims:

1. (Previously presented) A method for fabricating an electro-optical sensor, said method comprising:

providing a glass substrate comprising an optically smooth top surface and an optically smooth bottom surface;

coating the top surface of the glass substrate with a transparent electrode; applying a composition of electro-optic sensor material as a layer over the transparent electrode without using a transfer substrate;

applying a thin layer of adhesive over the layer of the electro-optic sensor material; and

applying a pellicle as a film bearing a dielectric mirror layer to the adhesive layer such that the dielectric mirror layer is substantially optically smooth against the electro-optic sensor material.

- (Original) The method in claim 1, wherein said electro-optic sensor material is a polymer dispersed liquid crystal (PDLC).
- (Currently amended) The method according to claim 1 wherein the laminating step comprises performing the lamination the pellicle is applied in a vacuum.
- (Original) The method according to claim 3 wherein the vacuum is less than 0.8 atmosphere.
- 5. (Original) The method according to claim 3 wherein the vacuum is between one-half atmosphere and 0.8 atmosphere.

Appln. No. 10/685,687 Amdt. dated August 2, 2006 Reply to Office Action of April 4, 2006

- 6. (Currently amended) The method according to claim 3 wherein the pellicle progressively engages the adhesive layer during the laminating step while being applied, the pellicle and the adhesive layer being disposed at an angle relative to one another.
- 7. (Currently amended) The method according to claim 1 wherein the pellicle progressively engages the adhesive layer during the laminating step while being applied, the pellicle and the adhesive layer being disposed at an angle relative to one another.
- 8. (Original) The method according to claim 7 wherein the vacuum is between one-half atmosphere and 0.8 atmosphere.